

Page 1 of 9

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.07.2019 / 0002

Replacing version dated / version: 01.06.2018 / 0001

Valid from: 24.07.2019 PDF print date: 24.07.2019 Marine Antifreeze 205 L

Art.: 25085

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Marine Antifreeze 205 L

Art.: 25085

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Anti-freeze

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Not applicable

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. **3.2 Mixture**



(B)

Page 2 of 9

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.07.2019 / 0002

Replacing version dated / version: 01.06.2018 / 0001

Valid from: 24.07.2019 PDF print date: 24.07.2019 Marine Antifreeze 205 L

Art.: 25085

| Registration number (REACH) | |
|---|--|
| Index | |
| EINECS, ELINCS, NLP | |
| CAS | |
| content % | |
| Classification according to Regulation (EC) 1272/2008 (CLP) | |

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions



Page 3 of 9

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.07.2019 / 0002

Replacing version dated / version: 01.06.2018 / 0001

Valid from: 24.07.2019 PDF print date: 24.07.2019 Marine Antifreeze 205 L

Art.: 25085

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13. Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Store at room temperature.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| © Chemical Name | Propane-1,2-diol | | Content %: |
|---------------------------------------|--------------------|-------------------------------------|------------|
| WEL-TWA: 150 ppm (474 mg/m3) | (total, vapour and | WEL-STEL: | |
| particulates), 10 mg/m3 (particulates | 3) | | |
| Monitoring procedures: | - | Draeger - Alcohol 100/a (CH 29 701) | |
| BMGV: | | Other information: | |

| Propane-1,2-diol | | | | | | |
|---------------------|--------------------------|------------------|------------|-------|-------|------|
| Area of application | Exposure route / | Effect on health | Descriptor | Value | Unit | Note |
| | Environmental | | | | | |
| | compartment | | | | | |
| | Environment - freshwater | | PNEC | 260 | mg/l | |
| | Environment - marine | | PNEC | 26 | mg/l | |
| | Environment - sewage | | PNEC | 20000 | mg/l | |
| | treatment plant | | | | | |
| | Environment - sediment, | | PNEC | 572 | mg/kg | |
| | freshwater | | | | | |
| | Environment - sediment, | | PNEC | 57,2 | mg/kg | |
| | marine | | | | | |
| | Environment - soil | | PNEC | 50 | mg/kg | |



(B)

Page 4 of 9

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.07.2019 / 0002

Replacing version dated / version: 01.06.2018 / 0001

Valid from: 24.07.2019 PDF print date: 24.07.2019 Marine Antifreeze 205 L

Art.: 25085

| | Environment - water, sporadic (intermittent) release | | PNEC | 183 | mg/l | |
|---------------------|--|-----------------------------|------|-----|-------|--|
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 213 | mg/kg | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 50 | mg/m3 | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 85 | mg/kg | |
| Consumer | Human - inhalation | Long term, local effects | DNEL | 10 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 168 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 10 | mg/m3 | |

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Safety gloves made of butyl (EN 374)

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Usual protective working garments

Respiratory protection:

^{(8) =} Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

^{(8) =} Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

^{** =} The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.



Page 5 of 9

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.07.2019 / 0002

Replacing version dated / version: 01.06.2018 / 0001

Valid from: 24.07.2019 PDF print date: 24.07.2019 Marine Antifreeze 205 L

Art.: 25085

Normally not necessary.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Blue, Clear Odour: Not determined Odour threshold: Not determined pH-value: Not determined Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined Flash point: >100 °C

Evaporation rate: Not determined Flammability (solid, gas): n.a.

Lower explosive limit:Not determinedUpper explosive limit:Not determinedVapour pressure:Not determinedVapour density (air = 1):Not determinedDensity:1,042 g/ml (20°C)

Bulk density: n.a.

Solubility(ies):
Water solubility:
Not determined
Partition coefficient (n-octanol/water):
Not determined
Auto-ignition temperature:
Not determined
Decomposition temperature:
Not determined

Viscosity: n.a.

Explosive properties: Product is not explosive.

Oxidising properties:

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Not determined

Not determined

Surface tension:

Not determined

Not determined

Not determined

Not determined

Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

Not to be expected

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid



Page 6 of 9

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 24.07.2019 / 0002

Replacing version dated / version: 01.06.2018 / 0001

Valid from: 24.07.2019 PDF print date: 24.07.2019 Marine Antifreeze 205 L Art.: 25085

None known **10.5 Incompatible materials**

None known

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

| Marine Antifreeze 205 L | | , | , | | | |
|----------------------------------|----------|-------|------|----------|-------------|--------|
| Art.: 25085 | | | | | | |
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin | | | | | | n.d.a. |
| sensitisation: | | | | | | |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - | | | | | | n.d.a. |
| single exposure (STOT-SE): | | | | | | |
| Specific target organ toxicity - | | | | | | n.d.a. |
| repeated exposure (STOT-RE): | | | | | | |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

| Propane-1,2-diol | | | | | | |
|----------------------------------|----------|--------|---------|----------|-------------|-------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >20000 | mg/kg | Rat | | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rabbit | | |
| Acute toxicity, by inhalation: | LC50 | >20 | mg/l/4h | Rabbit | | Vapours |
| Skin corrosion/irritation: | | | | | | Not irritant |
| Respiratory or skin | | | | | | Not sensitizising |
| sensitisation: | | | | | | |
| Germ cell mutagenicity: | | | | | in vitro | Negative |

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| Marine Antifreeze 205 L | | | | | | | |
|----------------------------|----------|------|-------|------|----------|-------------|--------|
| Art.: 25085 | | | | | | | |
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and | | | | | | | n.d.a. |
| degradability: | | | | | | | |
| 12.3. Bioaccumulative | | | | | | | n.d.a. |
| potential: | | | | | | | |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT | | | | | | | n.d.a. |
| and vPvB assessment | | | | | | | |
| 12.6. Other adverse | | | | | | | n.d.a. |
| effects: | | | | | | | |

| Pro | pane- | 1,2-d | liol |
|-----|-------|-------|------|
|-----|-------|-------|------|



Page 7 of 9

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.07.2019 / 0002

Replacing version dated / version: 01.06.2018 / 0001

Valid from: 24.07.2019 PDF print date: 24.07.2019 Marine Antifreeze 205 L

Art.: 25085

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--------------------------------------|-----------|------|--------|------|----------------------------------|--|--------------------------|
| 12.1. Toxicity to fish: | LC50 | 96h | 40613 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | LC50 | 48h | 18340 | mg/l | Ceriodaphnia spec. | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 7d | 13020 | mg/l | Ceriodaphnia spec. | , | |
| 12.1. Toxicity to algae: | EC50 | 48h | 19000 | mg/l | Pseudokirchneriell a subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 81,7 | % | | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | BCF | | 0,09 | | | | valued |
| Toxicity to bacteria: | NOEC/NOEL | 18h | >20000 | mg/l | Pseudomonas putida | | |
| Other information: | COD | | 1585 | mg/g | | | |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

16 01 15 antifreeze fluids other than those mentioned in 16 01 14

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a. Classification code: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:



Page 8 of 9

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.07.2019 / 0002

Replacing version dated / version: 01.06.2018 / 0001

Valid from: 24.07.2019 PDF print date: 24.07.2019 Marine Antifreeze 205 L

Art.: 25085

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 46,521 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 9. 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level

dw dry weight



Page 9 of 9

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 24.07.2019 / 0002

Replacing version dated / version: 01.06.2018 / 0001

Valid from: 24.07.2019 PDF print date: 24.07.2019 Marine Antifreeze 205 L

Art.: 25085

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.